

PULASTIC® ELITE RANGE

WOODEN SUBFLOORS WITH ULTIMATE
PERFORMANCE

PULASTIC®
SPORTS FLOORING

WWW.PULASTIC.COM

A SIKA COMPANY

PULASTIC® ELITE RANGE

Wooden subfloor systems providing outstanding comfort & safety for area- and combi-elastic sports floors



GREAT PERFORMANCE

The Pulastic® Elite range has been designed to provide the ultimate level in safety and comfort in Pulastic® sports flooring. In the Pulastic® Elite range you will find a perfect basis for a combination of all point-elastic Pulastic® sports floors with the area-elastic subfloors of this range.

THE ADVANTAGES OF THE PULASTIC® ELITE RANGE

- Ultimate level in safety and comfort
- Excellent long term resiliency for comfort and injury prevention
- Outstanding load bearing capacity and impact resistance
- Low total cost of ownership
- Very suitable for installation of floor heating and thermal insulation
- Wide range of toplayer finishes available, ranging from 2 mm to 9 mm, offering area- or combi-elastic characteristics
- Outstanding noise reduction (acoustic isolation) up to 29 dB
- Sustainable through renewable raw materials
- All wood products used are FSC labelled
- Pulastic® sports floors are manufactured under ISO 9001 for quality management, ISO 14001 for environmental care and CSR certified (ISO 26000 for corporate sustainability)

CHOOSING THE RIGHT FLOOR




All the floors of the Pulastic Elite range excel in comfort because of their resiliency. This will in any case help reduce fatigue and prevent injuries. And by choosing a floor system with the required need for load bearing capacity and impact resistance, the subfloors from the Elite range will contribute to a floor that will fit all your high level demands.

WOOD WITH A SEAMLESS CONSTRUCTION

The Pulastic Elite range is composed as follows:

- A special prefabricated shockpad in different grades
- Wooden multiply sheets in single or multilayer build-up, with or without tongued and grooved construction, ranging from 12 mm to 24 mm
- On top of the wooden subfloor, a seamless Pulastic sports floor up to 9 mm is being installed
- A silky matt water based sealcoat finishes the floor
- Additional line markings, logos and/or numbers on top of the sealcoat are applied, also with waterborne products

The final result is a seamless, easy to maintain, polyurethane sports floor with truly magnificent properties.



Name	Flooring type	Nominal thickness underconstruction	Comfort	Load bearing capacity	Options toplayer
Elite Comfort	Subfloor, wood	Up to 48 mm	2 - 9 mm Pulastic®
Elite Performance	Subfloor, wood	35 mm	2 - 9 mm Pulastic®
Elite Comfort UNO	Subfloor, wood	35 mm	2 - 9 mm Pulastic®